



Contact Rating	Contact Form/Material	2C, 4C / Ag Alloy		
	Contact Resistance	≤ 100mΩ @ 1A, 6 VDC		
	Contact Capacity	2C:- 10A 250VAC / 30VDC 4C:- 5A 250VAC / 30VDC		
Technical Specification	Insulation Resistance	≥ 500mΩ, (500VDC)		
	Dielectric Strength	≥ 1000VAC (Between Open Contact) / ≥ 1500VAC (Between Coil & Contact)		
	Operate, Release Time, Terminal Type	≤ 25ms, 25ms, PCB and Socket Mounting		
Coil Specification	Rated Coil Power	0.9W 1.2VA		
	Coil Voltage	5, 6, 12, 24, 48, 110VDC / 6, 12, 24, 48, 110, 220/240VAC		
Coil Data Chart	Nominal Voltage VDC	Pull in Voltage VDC	Release Voltage VDC	Coil Resistance Ω ±10%
	5	4.00	0.50	28
	6	4.80	0.60	40
	12	9.60	1.20	160
	24	19.20	2.40	640
	48	38.40	4.80	2560
	110	88.0	11.0	12100
	Nominal Voltage VAC	Pull in Voltage VAC	Release Voltage VAC	Coil Resistance Ω ±10%
	6	4.80	1.80	12
	12	9.60	3.60	42
	24	19.20	7.20	168
	48	38.40	14.40	675
	110	96.0	36.00	3500
220/240	176.00	66.00	14000/16500	

