



UT3400

Power MOSFET

5.8A, 30V N-CHANNEL ENHANCEMENT MODE POWER MOSFET

DESCRIPTION



The UTC **UT3400** is an N-ch enhancement MOSFET providing the customers with perfect $R_{DS(ON)}$ and low gate charge. This device can be operated with 2.5V low gate voltage.

The UTC **UT3400** is optimized for applications, such as a load switch or in PWM.

FEATURES

- * $R_{DS(ON)} \leq 28m\Omega$ @ $V_{GS}=10V$, $I_D=5.8A$
- $R_{DS(ON)} \leq 33m\Omega$ @ $V_{GS}=4.5V$, $I_D=5.0A$
- $R_{DS(ON)} \leq 52m\Omega$ @ $V_{GS}=2.5V$, $I_D=4.0A$

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UT3400L-AE3-R	UT3400G-AE3-R	SOT-23	G	S	D	Tape Reel

Note: Pin Assignment: G: Gate S: Source D: Drain

UT3400G-AE3-R		(1)Packing Type	(1) R: Tape Reel
		(2)Package Type	(2) AE3: SOT-23
		(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	5.8	A
Pulsed Drain Current (Note 2)	I_{DM}	30	A
Power Dissipation	P_D	1.4	W
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating : Pulse width limited by maximum junction temperature.

3. Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 0.5\%$.

■ THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction to Ambient (Note)	θ_{JA}		85	125	$^{\circ}\text{C/W}$

Note: Surface mounted on 1 in² copper pad of FR4 board with 2oz





■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	30			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±12V, V _{DS} =0V			100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	0.7	1.1	1.4	V
On-State Drain Current	I _{D(ON)}	V _{DS} =5V, V _{GS} =4.5V	30			A
Drain to Source On-state Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =5.8A		22.8	28	mΩ
		V _{GS} =4.5V, I _D =5A		27.3	33	mΩ
		V _{GS} =2.5V, I _D =4 A		43.3	52	mΩ
DYNAMIC PARAMETERS						
Input Capacitance	C _{ISS}	V _{DS} =15V, V _{GS} =0V, f =1MHz		823		pF
Output Capacitance	C _{OSS}			99		pF
Reverse Transfer Capacitance	C _{RSS}			77		pF
Gate Resistance	R _G	V _{GS} =0V, V _{DS} =0V, f =1MHz		1.2		Ω
SWITCHING PARAMETERS						
Total Gate Charge	Q _G	V _{GS} =4.5V, V _{DS} =15V, I _D =5.8A		9.7		nC
Gate Source Charge	Q _{GS}			1.6		nC
Gate Drain Charge	Q _{GD}			3.1		nC
Turn-ON Delay Time	t _{D(ON)}	V _{GS} =10V, V _{DS} =15V R _L =2.7Ω, R _{GEN} =6Ω		5.5		ns
Turn-ON Rise Time	t _R			5.1		ns
Turn-OFF Delay Time	t _{D(OFF)}			37		ns
Turn-OFF Fall-Time	t _F			4.2		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Diode Continuous Forward Current (Note 1)	I _S				2.5	A
Drain-Source Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V		0.71	1	V
Reverse Recovery Time	t _{rr}	I _F =5A, dI/dt =100A/μs		16		ns
Reverse Recovery Charge	Q _{rr}			8.9		nC

Notes: 1. Repetitive Rating : Pulse width limited by maximum junction temperature.

2. Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 0.5\%$.

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.